



## 50 PSI High Flow Fuel Nozzle Multi Cylinder Engine Fuel Pump Nozzle

Our Product Introduction

For more products please visit us on [refueling-equipment.com](http://refueling-equipment.com)

### Basic Information

- Place of Origin: China
- Brand Name: Virette



### Product Specification

- Features: Trigger Lock, Splash Guard, Automatic Shut-off
- Pressure Rating: 50 Psi
- Stamp Number: Dlla150s187
- Flow Rate: 10 Gallons Per Minute
- Certifications: UL, CSA, CE
- Component: Fuel Injection Device
- Cylinder: Multi-cylinder
- Temperature Rating: 0-150 Degrees Fahrenheit
- Highlight: 50 psi high flow fuel nozzle ,  
high flow fuel nozzle multi cylinder ,  
50 psi fuel pump nozzle

## Product Description

### 50 PSI Pressure Rating High Flow Oil Delivery Spout for Multi Cylinder Engines

#### Product Description:

The Fuel Nozzle comes in the 11A model and is designed with various features to make petroleum handling more efficient and safe. One of its standout features is the Trigger Lock, which allows the user to lock the nozzle in place while dispensing fuel, reducing hand fatigue and improving accuracy. Additionally, the Fuel Nozzle also comes with a Splash Guard, which helps prevent fuel from splashing back during dispensing, keeping the working area clean and safe from fire hazards.

The Fuel Nozzle is also designed with an Automatic Shut-off feature, which automatically stops the flow of fuel once the tank is full, preventing overfilling and spillage. This feature not only improves safety but also helps save time and money by preventing wastage of fuel.

The Fuel Nozzle has been certified by various regulatory bodies, including UL, CSA, and CE, ensuring that it meets the highest safety standards and is suitable for use in various industries. These certifications give users peace of mind and assurance that they are using a product that has been rigorously tested and meets all safety requirements.

The Fuel Nozzle also comes with a quality guarantee, assuring users that they are purchasing a product that has been designed and manufactured to meet the highest quality standards. This guarantee ensures that the Fuel Nozzle is a reliable and durable product that can withstand the rigors of daily use in various petroleum handling industries.

#### Features:

Product Name: Fuel Nozzle

Quality: Guaranteed

Pressure Rating: 50 Psi

Cylinder: Multi-cylinder

Size: 5.5 Inches

Material: Aluminum

This Fuel Nozzle is a high-quality gas pump spout that guarantees a smooth petroleum flow nozzle. It has a pressure rating of 50 Psi and is designed with multi-cylinder technology. The Fuel Nozzle measures 5.5 inches and is made of durable aluminum, making it a reliable oil delivery spout for your needs.

#### Technical Parameters:

Quality	Guaranteed
Temperature Rating	0-150 Degrees Fahrenheit
Features	Trigger Lock, Splash Guard, Automatic Shut-off
Flow Rate	10 Gallons Per Minute
Cylinder	Multi-cylinder
Size	5.5 Inches
Component	Fuel Injection Device
Nozzle Diameter	1 Inch
Pressure Rating	50 Psi
Warranty	1 Year Limited Warranty

#### Applications:

Trigger Lock: This feature allows you to lock the nozzle in place, making it easier to control the flow of petroleum products and reducing the risk of spills.

Splash Guard: The built-in splash guard helps to prevent spills and keeps the fuel flowing smoothly, even in rough conditions.

Automatic Shut-off: The automatic shut-off feature ensures that the nozzle stops dispensing fuel when the tank is full, reducing the risk of overflows and spills.

The Virette Fuel Nozzle is designed to handle pressures of up to 50 psi, making it ideal for use in a wide range of settings. Whether you are refueling a car at a gas station or filling up a tank at a construction site, this nozzle is up to the task. The model 11A nozzle has a diameter of 1 inch, which is perfect for use with most gasoline hose nozzles. Additionally, this nozzle has a flow rate of 10 gallons per minute, which means that you can fill up tanks quickly and efficiently.

Overall, the Virette Fuel Nozzle is a versatile and reliable product that is perfect for anyone who needs to transfer petroleum products safely and efficiently. Some of the occasions and scenarios where this nozzle can be used include:

Gas stations: This nozzle is perfect for use in gas stations, where it can be used to refuel cars, trucks, and other vehicles.

Construction sites: Whether you are running heavy machinery or powering generators, this nozzle is up to the task of delivering fuel where it is needed.

Marinas: Boats and other watercraft require fuel, and this nozzle is perfect for use in marinas and other waterfront locations.

Agriculture: From tractors to other farm equipment, this nozzle is ideal for transferring fuel in the agricultural industry.

With its high-quality construction, reliable performance, and versatile design, the Virette Fuel Nozzle is a must-have tool for anyone who needs to transfer petroleum products safely and efficiently.

### Customization:

Customize your gasoline hose nozzle with Virette! Our fuel nozzle product is made of high-quality aluminum and guaranteed to give you the best performance. With a flow rate of 10 gallons per minute, you can trust that our oil delivery spout will get the job done quickly and efficiently.

Our petroleum flow nozzle is certified by UL, CSA, and CE, ensuring top-rated safety and quality. We take pride in our product's place of origin, China, and offer a 1-year limited warranty for your peace of mind.

Don't settle for a standard nozzle - customize your Virette fuel nozzle today and experience the best in fuel dispensing technology.

### Packing and Shipping:

#### Product Packaging:

One Fuel Nozzle

Product Manual

Protective Cap

#### Shipping Information:

Shipping Weight: 2 lbs

Shipping Dimensions: 10" x 6" x 4"

Shipping Carrier: UPS

Delivery Time: 3-5 Business Days



**Virette Technology Co., Ltd.**



+8615651807973



ryan.s@youngtiontech.com



refueling-equipment.com

Shizishu Industrial Concentration Zone, GuxiongStreet, Yuhuatai District, Nanjing City, Jiangsu Province, China